

MEMORANDUM

DEPARTMENT OF ENVIRONMENTAL QUALITY Piedmont Regional Office 4949-A Cox Road Glen Allen, Virginia 23060

SUBJECT: Flow Frequency Determination / 303(d) Status

Picture Lake Campground - VA0070564

TO: Janine Howard

FROM: Jennifer Palmore, P.G.

DATE: February 3, 2011

COPIES: File

The Picture Lake Campground discharges to Picture Branch in Dinwiddie County, VA. The outfall is located at rivermile 5APCT001.23. Flow frequencies have been requested at this site for use in developing effluent limitations for the VPDES permit.

The USGS conducted 14 flow measurements on Hatcher Run from 1998 through 2007. The measurements were made at the Route 627 bridge near Five Forks, VA (#02046265). The measurements were correlated with the same day daily mean values from the continuous record gage on Stony Creek near Dinwiddie. VA (#02046000). The measurements and daily mean values were plotted on a logarithmic graph and a best fit power trend line was plotted through the data points. The required flow frequencies from the reference gage were plugged into the equation for the regression line and the associated flow frequencies at the measurement site were calculated. The flow frequencies for Hatcher Run were then projected to Picture Branch by drainage area proportion. The data for the reference gage, measurement site, and discharge point are presented below and the regression analysis is attached.

Stony Creek near Dinwiddie, VA (#02046000):

Drainage area:112 mi2 Statistical period: 1946-2003 High flow months: Jan-Apr

1Q30 = 0.12 cfsHigh Flow 1Q10 = 14 cfs 1010 = 0.26 cfsHigh Flow 7Q10 = 18 cfs7Q10 = 0.31 cfsHigh Flow 30Q10 = 32 cfsHM = undetermined 30Q10 = 0.77 cfs30Q5 = 1.6 cfs

Hatcher Run at Route 627 near Five Forks, VA (#02046265):

Drainage area = 6.77 mi²

1Q30 = 0.00 cfsHigh Flow 1Q10 = 0.80 cfs High Flow 7Q10 = 1.07 cfs 1Q10 = 0.01 cfs7Q10 = 0.01 cfsHigh Flow 30Q10 = 2.09 cfs HM = undetermined 30Q10 = 0.03 cfs

30Q5 = 0.07 cfs

Picture Branch at discharge point:

Drainage area = 3.50 mi²

1Q30 = 0.00 cfs (0.00 MGD)	High Flow $1Q10 = 0.42 \text{ cfs } (0.27 \text{ MGD})$
1Q10 = 0.00 cfs (0.00 MGD)	High Flow $7Q10 = 0.56 \text{ cfs } (0.36 \text{ MGD})$
7Q10 = 0.01 cfs (0.00 MGD)	High Flow 30Q10 = 1.1 cfs (0.70 MGD)
30Q10 = 0.01 cfs (0.01 MGD)	HM = undetermined
30Q5 = 0.03 cfs (0.02 MGD)	

The values at the discharge point were determined by drainage area proportions and do not address any withdrawals, discharges, or springs.

Please note that the discharge is located directly below Picture Lake dam. D.X. Ren states in his 4/12/1991 modeling memorandum that "The dam releases water via a spray nozzle. According to the operator, during the summer season, the dam reduces water flow. [The} flow analysis assumed outflow from the impoundment equalled (sic) inflow to the Lake. It is possible that actual low flow for this stream could be different from [the] calculated 7Q10 flow due to the effect on flows of the impoundment." Ren proceeded to use a previously-used 7Q10 flow of 0.0337 cfs for the model. Since the currently calculated flow is considerably less than the flow that was used for modeling, the calculated values should be used.

In addition, please note that previous flow analyses used measurements on Whipponock Creek. During this reissuance, I determined that a flow measurement on Whipponock was not included in the 1985 USGS Water Resources Data report and was therefore excluded from the previous analyses. Once this measurement was included, the correlation between Whipponock and Stony Creek was not acceptable for use (R = 0.783). The 2007 measurements collected on Hatcher Run enabled this site to be used this cycle. This site is a better choice as it is located within the same watershed as the discharge and there is a strong correlation between the measurements and Stony Creek (R = 0.934).

During the 2008 and draft 2010 305(b)/303(d) Water Quality Assessments, Picture Branch was assessed as a Category 2A water ("Waters are supporting all of the uses for which they were monitored.") The Aquatic Life Use is fully supporting and the Recreation-, Fish Consumption-, and Wildlife Uses were not assessed.

The stream is not included in any approved TMDL.


Picture Branch has historically been considered a Tier 1 water. Antidegradation was not applied during modeling efforts.

Ambient water quality data is attached for your use in developing permit limits. Field data was collected at station 5APCT001.23, which is located on Picture Branch at the Route 1 bridge near the outfall. However, hardness was not collected at this station; therefore hardness data from station 5AHRA010.94 is included. This station is located on Hatcher Run at the Route 631 bridge (Picture Branch is a tributary of Hatcher Run).

If you have any questions concerning this analysis, please let me know.

Hatcher Run at Route 627, near Five Forks, VA #02046265 vs Stony Creek near Dinwiddie, VA #02046000

Regression Analysis



Flow Data (cfs)		
<u>Date</u>	Stony	<u>Hatcher</u>
9/10/1998	2.5	0.027
12/9/1998	6.2	0.541
2/9/1999	42	3.50
6/22/1999	12	3.68
1/30/2007	77	4.52
2/22/2007	103	8.05
3/6/2007	101	5.94
4/5/2007	58	3.60
5/25/2007	38	2.23
7/16/2007	2.8	0.035
8/7/2007	12	1.01
9/12/2007	4.7	0.340
9/26/2007	4.0	0.072
10/11/2007	0.80	0.096

Regression Statis	tics
Multiple R	0.934
R Square	0.873
Adjusted R Square	0.862
Standard Error	0.949
Observations	14


Flow F	requencies (cfs)	
Stony		<u>Hatcher</u>	<u>Picture</u>
0.12	1Q30	0.00	0.00
0.26	1Q10	0.01	0.00
0.31	7Q10	0.01	0.01
0.77	30Q10	0.03	0.01
1.6	30Q5	0.07	0.03
14	HF 1Q10	0.80	0.42
18	HF 7Q10	1.07	0.56
32	HF 30Q10	2.09	1.1
	HM		
112	DA (mi ²) Jan-Apr	6.77	3.50



TREATMENT PLANT FLOW DIAGRAM

Grit Chamber Chamber (Comminutor) Camparound - SLODGE RETUR N-Chlorine existing 106 Clarifier Aerativa Surge tank house Y-NOTCH WEIT Studge dechlorinator holding Picture Branch SITE PLAN n.t.s.

FIGURE 1




Attachment C: Topographic Map, Sutherland Quadrangle (70A) and Aerial Image


FACILITY NAME: H & B of Virginia, Inc. VPDES PERMIT NUMBER: VA0070564

PICTURE LAKE CAMPGROUND

SECTION A - 5




TOPOGRAPHIC MAP OF AREA FOLLOWS





Aerial image of Picture Lake



Topographic Map (Sutherland Quadrangle 70A)



Virginia Department of Environmental Quality

WASTEWATER FACILITY INSPECTION REPORT

FACILITY NAM	ME:		INSPECTION DATE:	October 20,	<u> 2010</u>
Picture Lake C	ampground WWTP		INSPECTOR	Mike Dare	
PERMIT No.:	VA0070564		REPORT DATE:	October 25,	2010
TYPE OF FACILITY:	MunicipalIndustrial	Small Minor	TIME OF INSPECTION: TOTAL TIME SPENT	Arrival 1245 12 hours	Departure 1440
	☐ Federal		(including prep & travel)	12 110010	
PHOTOGRAPH	HS: ▼ Yes	□ No	UNANNOUNCED INSPECTION	ON?	es 🔽 No
REVIEWED B	Y / Date:				
PRESENT DU	RING INSPECTION:	Ryan Porte	<u>er</u>		_

TECHNICAL INSPECTION

1.	Has there been any new construction?	☐ Yes	▼ No
	If so, were plans and specifications approved?	1 105	1110
	Comments:		
2.	Is the Operations and Maintenance Manual approved and up-to-date?	▼ Yes	■ No
	Comments:		
3.	Are the Permit and/or Operation and Maintenance Manual specified licensed	▼ Yes	□ No
	operator being met?	100	110
	Comments: An Operator requirement is not specified in the current permit		
4.	Are the Permit and/or Operation and Maintenance Manual specified operator	▼ Yes	□ No
	staffing requirements being met?	14 103	110
	Comments: The facility is checked daily by campground personnel and		
	weekly by a certified Operator.		
5.	Is there an established and adequate program for training personnel?	▼ Yes	□ No
	Comments: OJT and DEQ Operator Assistance Training	103	140
6.	Are preventive maintenance task schedules being met?	▼ Yes	□ No
	Comments:	108	110
7.		☐ Yes	▼ No
	Comments:	1 1 68	INO
8.	Has there been any bypassing or overflows since the last inspection?	☐ Yes	▼ No
	Comments:	105	110
9.	Is the standby generator (including power transfer switch) operational and exercised	☐ Yes	□ No
	regularly?	105	110
	Comments: N/A; there is no standby generator. Mr. Porter reported that a		
	portable generator is available at the campground.		
10	. Is the plant alarm system operational and tested regularly?	☐ Yes	□ No
	Comments: NA; the plant is not equipped with an alarm system.	103	110

VA DEQ Wastewater Facility Inspection Report

Permit #	VA0070564
----------	-----------

TECHNICAL INSPECTION

11. Is sludge disposed of in accordance with the approved sludge management plan? Comments: Sludge is removed periodically by a septic hauler for discharge at		
a regional wastewater treatment plant.		
12. Is septage received? ☐ Yes No		
If so, is septage loading controlled, and are appropriate records		
maintained?		
Comments:		
13. Are all plant records (operational logs, equipment maintenance, industrial waste contributors, sampling and testing) available for review and are records adequate? ☐ Yes No		
Comments: The maintenance of an operational log was recently		
discontinued. Resumption is recommended.		
14. Which of the following records does the plant maintain?		
☐ Operational logs ☐ Instrument maintenance & calibration		
☐ Mechanical equipment maintenance ☐ Industrial Waste Contribution (Municipal facilities)		
Comments:		
15. What does the operational log contain?		
☐ Visual observations ☐ Flow Measurement ☐ Laboratory results ☐ Process adjustments		
Control calculations Other (specify)		
Comments: Above maintained on bench sheets.		
16. What do the mechanical equipment records contain?		
☐ As built plans and specs ☐ Manufacturers instructions ☐ Lubrication schedules		
▼ Spare parts inventory □ Equipment/parts suppliers		
☐ Other (specify)		
Comments:		
17. What do the industrial waste contribution records contain (Municipal only)?		
☐ Waste characteristics ☐ Impact on plant ☐ Locations and discharge types		
☐ Other (specify)		
Comments: N/A		
18. Which of the following records are kept at the plant and available to personnel?		
☐ Equipment maintenance records ☐ Operational log ☐ Industrial contributor records		
▼ Instrumentation records		
Comments:		
19. List records not normally available to plant personnel and their location:		

VA DEQ Wastewater Facility Inspection Report

Permit #	VA0070564
I CIIIII m	V AUU I UUUT

UNIT PROCESS EVALUATION SUMMARY SHEET

UNIT PROCESS	APPLICABLE	PROBLEM S*	COMMENTS
Sewage Pumping			
Flow Measurement (Influent)			
Screening/Comminution	Yes		
Grit Removal			
Oil/Water Separator			
Flow Equalization			
Ponds/Lagoons			
Imhoff Tank			
Primary Sedimentation			
Trickling Filter			
Septic Tank and Sand Filter			
Rotating Biological Contactor			
Activated Sludge Aeration	Yes		
Biological Nutrient Removal	163		
Sequencing Batch Reactor			
Secondary Sedimentation	Yes		
Flocculation	162		
Tertiary Sedimentation			
Filtration			
Micro-Screening			
Activated Carbon Adsorption			
Chlorination	Vaa		
Dechlorination	Yes	•	One take is mission a sec
Ozonation	Yes	6	One tube is missing a cap
Ultraviolet Disinfection			
Post Aeration	Yes		Step aerator
Flow Measurement (Effluent)	Yes		Estimated
Land Application (Effluent)			
Plant Outfall	Yes		
Sludge Pumping			
Flotation Thickening (DAF)			
Gravity Thickening			
Aerobic Digestion	Yes		Sludge holding tank
Anaerobic Digestion			
Lime Stabilization			
Centrifugation			
Sludge Press			
Vacuum Filtration			
Drying Beds			
Thermal Treatment			
Incineration			
Composting			
Land Application (Sludge)			

- **Problem Codes**
- 1. Unit Needs Attention
- 2. Abnormal Influent/Effluent
- 3. Evidence of Equipment Failure

- 4. Unapproved Modification or Temporary Repair
- 5. Evidence of Process Upset6. Other (explain in comments)

Permit #

VA0070564

INSPECTION PHOTOS



Package plant consists of aeration, clarifier and sludge holding basins. Bleach addition system is at far right.



Raw sewage enters aeration basin at center of photo



A thick dark foam has accumulated at one corner of the aeration basin



A layer of solids covers much of clarifier surface



Sodium bisulfite tablet dechlorination system



Plant outfall at the Picture Branch

VA DEQ Wastewater Facility Inspection Report

F &	Permit #	VA0070564
-----	----------	-----------

EFFLUENT FIELD DATA:

Flow	0.003 MGD	Dissolved Oxygen	6.76 mg/L	TRC (Contact Tank)	mg/L
рН	6.0 S.U.	Temperature	<u>18.6</u> ∘C	TRC (Final Effluent)	0.00 mg/L
	a Sampling Inspection ucted?	Yes	(see Sampling Inspec	ction Report) No	

CONDITION OF OUTFALL AND EFFLUENT CHARACTERISTICS:

1.	Type of outfall: Shore based ☐ Submerged	Diffuser?	▽ No
2.	Are the outfall and supporting structures in good	condition? Yes	□ No
3.	Final Effluent (evidence of following problems):	☐ Sludge bar	☐ Grease
	☐ Turbid effluent ☐ Visible foam	☐ Unusual color	☐ Oil sheen
4.	Is there a visible effluent plume in the receiving s	tream?	▽ No
5.	 ✓ No observed problems Receiving stream: Comments: Receiving stream appeared clear. 	☐ Indication of proble	

REQUIRED CORRECTIVE ACTIONS:

- 1. Maintenance of an operational log was recently discontinued. Resumption is recommended. The operational log should include at a minimum: names/times of Operator attendance, visual observations, process adjustments and equipment maintenance.
- 2. One of the dechlorination system tablet feeder tubes is missing a cap. The cap should be replaced.
- 3. The pH of the plant effluent was 6.0 at the time of inspection. Plant effluent pH results indicated on the September 2010 DMR range from 6 to 9. Please discuss possible methods to reduce this wide fluctuation. e.g., If lime is being added to the aeration basin in large single applications, smaller more routine applications would be recommended.

NOTES and COMMENTS:

The characteristics of the solids at this plant are that of an old, over-oxidized sludge - dark brown mixed liquor, a patch of thick dark foam on the aeration basin, light, fluffy solids on the surface of the clarifier and a slightly turbid effluent. This is contradicted by process control test results that indicate a younger sludge - low settleability (200 ml/L) and low MLSS (1900 mg/L). BOD₅, TSS and Ammonia results reported on the DMR for September 2010 were well below permit limits. No changes in operation are recommended by this writer at this time. Jason Spicer of DEQ's Operator Training and Assistance Program concurred with this approach when contacted by phone on October 25, 2010. Mr. Spicer pointed out that indicators typical to most activated sludge plants may not be appropriate here due to the age and limited treatment capability of this facility. Continued weekly process control testing by a certified Operator is strongly encouraged.

Attachment E: DMR data, Application (EPA Form 2A) data, Ambient Stream Data

Effluent (DMR) data

Flow Average (MGD)	Flow Maximum (MGD)	pH (min) S.U.	pH (max) S.U.	Dissolved Oxygen (min) (mg/l)	DMR Due Date
0.0029	0.0029	7	7	7	10-Nov-06
0.0028	0.0029	7	7	7	10-Dec-06
0.0028	0.0029	7	7	7	10-Jan-07
0.0029	0.0029	7	7	7	10-Feb-07
0.0029	0.0029	7	7	7	10-Mar-07
0.0029	0.0029	7	8	7	10-Apr-07
0.0029	0.0029	7	7	7	10-May-07
0.0029	0.0029	7	7	7	10-Jun-07
0.0029	0.0029	7	8	7	10-Jul-07
0.0033	0.0058	7	8	NULL	10-Aug-07
0.0031	0.0058	7	8	7	10-Sep-07
0.0029	0.0029	7	8	7	10-Oct-07
0.0033	0.0058	7	8	7	10-Nov-07
0.003	0.003	7	8	7	10-Dec-07
0.0029	0.0058	7	8	7	10-Jan-08
0.0029	0.0029	7	7	7	10-Feb-08
0.0029	0.0029	7	8	7	10-Mar-08
0.0041	0.0058	7	8	7	10-Apr-08
0.0055	0.0058	7	7	7	10-May-08
0.0057	0.0058	7	8	7	10-Jun-08
0.0058	0.0058	7	7	0.8	10-Jul-08
0.0058	0.0058	7	7	7	10-Aug-08
0.0058	0.0058	7	7	7	10-Sep-08
0.0058	0.0058	7	7	7	10-Oct-08
0.0058	0.0058	7	8	7	10-Nov-08
0.0058	0.0058	7	8	7	10-Dec-08
0.0038	0.0058	7	7	7	10-Jan-09
0.0029	0.0029	7	7	7	10-Feb-09

Flow Average	Flow Maximum	pH (min)	pH (max)	Dissolved Oxygen	DMR Due Date
(MGD) 0.0029	(MGD) 0.0029	S.U.	S.U.	(min) (mg/l)	10-Mar-09
0.0029	0.0029	,	,	,	10-Iviai-03
0.0029	0.0029	7	7	7	10-Apr-09
0.0029	0.0029	7	7	7	10-May-09
0.0029	0.0029	7	7	7	10-Jun-09
0.0029	0.0029	7	7	7	10-Jul-09
0.0029	0.0029	6	8	7	10-Aug-09
0.0029	0.0029	7	8	7	10-Sep-09
0.0029	0.0029	7	7.8	7	10-Oct-09
0.0029	0.0029	7	7	7	10-Nov-09
0.0033	0.0043	7	7	7	10-Dec-09
0.001	0.0029	6	9	7	10-Jan-10
0.0007	0.0007	7	9	9.7	10-Feb-10
0.0007	0.0007	7	9	9.7	10-Mar-10
0.0007	0.0007	7	9	9.7	10-Apr-10
0.0029	0.0029	6	9	7	10-May-10
0.0029	0.0029	7	9	1.6	10-Jun-10
0.0029	0.0029	6	9	8	10-Jul-10
0.0029	0.0029	6	9	8	10-Aug-10
0.0029	0.0029	6	9	7	10-Sep-10
0.0029	0.0029	6	9	7	10-Oct-10
0.0029	0.0029	6	9	NULL	10-Nov-10
0.0029	0.0029	6.3	7.2	6.1	10-Dec-10
			Max 10 th Percentile: 7		
			Max 90 th percentile: 9		

Monthly Average DMR data

BOD _s (mg/l)	TSS (mg/l)	TRC (mg/l)	Ammonia-N (mg/l)	DMR Due Date
10.8	5.2	<ql< td=""><td>Staring with 10-Jun-09 DMR</td><td>10-Nov-06</td></ql<>	Staring with 10-Jun-09 DMR	10-Nov-06
9	2.2	<ql< td=""><td></td><td>10-Dec-06</td></ql<>		10-Dec-06
10.7	10	<ql< td=""><td></td><td>10-Jan-07</td></ql<>		10-Jan-07
13.9	3.8	<ql< td=""><td></td><td>10-Feb-07</td></ql<>		10-Feb-07
8.4	1.2	<ql< td=""><td></td><td>10-Mar-07</td></ql<>		10-Mar-07
5.9	3	<ql< td=""><td></td><td>10-Apr-07</td></ql<>		10-Apr-07
16.5	9.4	<ql< td=""><td></td><td>10-May-07</td></ql<>		10-May-07
<2.0	2.4	<ql< td=""><td></td><td>10-Jun-07</td></ql<>		10-Jun-07
5.8	2.2	<ql< td=""><td></td><td>10-Jul-07</td></ql<>		10-Jul-07
4.6	18.2	<ql< td=""><td></td><td>10-Aug-07</td></ql<>		10-Aug-07
3.7	4.8	<ql< td=""><td></td><td>10-Sep-07</td></ql<>		10-Sep-07
3.8	1.5	<ql< td=""><td></td><td>10-Oct-07</td></ql<>		10-Oct-07
4.5	3.1	1		10-Nov-07
2.2	1.4	<ql< td=""><td></td><td>10-Dec-07</td></ql<>		10-Dec-07
31.4	6	<ql< td=""><td></td><td>10-Jan-08</td></ql<>		10-Jan-08
12	13.2	<ql< td=""><td></td><td>10-Feb-08</td></ql<>		10-Feb-08
12.8	4.4	<ql< td=""><td></td><td>10-Mar-08</td></ql<>		10-Mar-08
5.5	2.5	<ql< td=""><td></td><td>10-Apr-08</td></ql<>		10-Apr-08
14	<1.0	<ql< td=""><td></td><td>10-May-08</td></ql<>		10-May-08
3.5	5.6	<ql< td=""><td></td><td>10-Jun-08</td></ql<>		10-Jun-08
<3.0	<1.0	<ql< td=""><td></td><td>10-Jul-08</td></ql<>		10-Jul-08
3.6	1.2	<ql< td=""><td></td><td>10-Aug-08</td></ql<>		10-Aug-08
<3.0	<1.0	<ql< td=""><td></td><td>10-Sep-08</td></ql<>		10-Sep-08
3.6	3.5	<ql< td=""><td></td><td>10-Oct-08</td></ql<>		10-Oct-08
3.2	1.7	<ql< td=""><td></td><td>10-Nov-08</td></ql<>		10-Nov-08
4	3.8	<ql< td=""><td></td><td>10-Dec-08</td></ql<>		10-Dec-08
<1.0	2.9	<ql< td=""><td></td><td>10-Jan-09</td></ql<>		10-Jan-09

BOD _s (mg/l)	TSS (mg/l)	TRC (mg/l)	Ammonia-N (mg/l)	DMR Due Date
4.4	5.7	<ql< td=""><td></td><td>10-Feb-09</td></ql<>		10-Feb-09
<3.0	10.5	<ql< td=""><td></td><td>10-Mar-09</td></ql<>		10-Mar-09
<3.0	7.8	<ql< td=""><td></td><td>10-Apr-09</td></ql<>		10-Apr-09
<2.0	4.2	<ql< td=""><td></td><td>10-May-09</td></ql<>		10-May-09
27.7	10.1	<ql< td=""><td>9.5</td><td>10-Jun-09</td></ql<>	9.5	10-Jun-09
4.1	3	<ql< td=""><td>3.1</td><td>10-Jul-09</td></ql<>	3.1	10-Jul-09
2.4	4.4	CL2, INST TECH MIN LIMIT	15.6	10-Aug-09
31.2	1.6	<ql< td=""><td>0.1</td><td>10-Sep-09</td></ql<>	0.1	10-Sep-09
15.6	2	<ql< td=""><td>3.55</td><td>10-Oct-09</td></ql<>	3.55	10-Oct-09
5.1	4	<ql< td=""><td>1.06</td><td>10-Nov-09</td></ql<>	1.06	10-Nov-09
8.6	6	<ql< td=""><td>26.5</td><td>10-Dec-09</td></ql<>	26.5	10-Dec-09
11.7	17	<ql< td=""><td>1.78</td><td>10-Jan-10</td></ql<>	1.78	10-Jan-10
13.2	11	<ql< td=""><td>0.23</td><td>10-Feb-10</td></ql<>	0.23	10-Feb-10
8.5	24.8	<ql< td=""><td>0.14</td><td>10-Mar-10</td></ql<>	0.14	10-Mar-10
9.3	18	<ql< td=""><td>0.46</td><td>10-Apr-10</td></ql<>	0.46	10-Apr-10
4.4	8.5	<ql< td=""><td>2.5</td><td>10-May-10</td></ql<>	2.5	10-May-10
20.8	13.6	<ql< td=""><td>7.96</td><td>10-Jun-10</td></ql<>	7.96	10-Jun-10
26.8	25.6	<ql< td=""><td>40.6</td><td>10-Jul-10</td></ql<>	40.6	10-Jul-10
3.9	11.8	<ql< td=""><td>0.4</td><td>10-Aug-10</td></ql<>	0.4	10-Aug-10
<2.0	18.5	<ql< td=""><td>0.16</td><td>10-Sep-10</td></ql<>	0.16	10-Sep-10
2.3	3.7	<ql< td=""><td>0.37</td><td>10-Oct-10</td></ql<>	0.37	10-Oct-10
4.8	12.1	NULL	0.57	10-Nov-10
19.7	25	<ql< td=""><td>2.86</td><td>10-Dec-10</td></ql<>	2.86	10-Dec-10

Application (EPA Form 2A) data

Parameter	Maximum Daily Value		Average Daily Value		
	Value	Units	Value	Units	No. Samples
pH (minimum)	6.0	S.U.			
pH (maximum)	9.0	S.U.			
Flow Rate	0.0029	MGD	0.0023	MGD	334
Temperature (Winter)	14	°C	UNK	NA	Estimate
Temperature (Summer)	24	°C	UNK	NA	Estimate

Pollutant	Maximum Daily Discharge		Average Daily Discharge		
	Conc.	Units	Conc.	Units	No. Samples
BOD ₅	26.8	mg/l	10.5	mg/l	11
Fecal Coliform	<2	N/100 ml	<2	N/100 ml	3
TSS	25.6	mg/l	15.7	mg/l	11

Ambient Stream Data

	Collection		Temp	Field	Do
Station ID	Date	Depth	Celcius	Ph	Probe
5APCT001.23	7/13/1994	0.3	27.74	6.51	3.94
5APCT001.23	1/23/2006	0.3	7.03	6.02	10.32
5APCT001.23	2/14/2006	0.3	6.15	6.13	11.01
5APCT001.23	3/22/2006	0.3	8	6.7	9.4
5APCT001.23	4/24/2006	0.3	20.2	6.1	6.1
5APCT001.23	5/23/2006	0.3	18.4	6.1	5.4
5APCT001.23	6/29/2006	0.3	28.1	6.1	5.6
5APCT001.23	7/18/2006	0.3	28.8	6.3	4.7
5APCT001.23	8/21/2006	0.3	24.4	6.7	4.5
90th					
Percentile			28.2	6.7	
10th					
Percentile			6.9	6.1	

	Collection Date		HARDNESS, TOTAL
Station ID	Time	Depth	(MG/L AS CACO3)
5AHRA010.94	06/12/2001 13:30	0.3	11.5
	08/13/2001 17:15	0.3	27.9
	10/23/2001 16:00	0.3	15.1
	12/05/2001 16:20	0.3	10.2
	02/21/2002 15:00	0.3	19.1
	04/02/2002 15:48	0.3	10
	06/20/2002 15:45	0.3	37.2
	07/16/2002 11:30	0.3	45.5
	09/19/2002 15:35	0.3	24.5
	11/25/2002 14:20	0.3	12.1
	01/15/2003 14:15	0.3	10.7
	03/20/2003 16:00	0.3	16.6
	05/14/2003 15:00	0.3	20.7
	01/18/2007 12:10	0.3	10
	03/21/2007 11:15	0.3	10
	05/30/2007 11:05	0.3	23
Mean			19.0

Attachment F: MSTRANTI data source report, MSTRANTI, Stats.exe results

MSTRANTI DATA SOURCE REPORT

Stream information			
Mean Hardness	Ambient Stream Data (Station 5AHRA010.94)		
90% Temperature (annual)	Ambient Stream Data (Station 5APCT001.23)		
90% Temperature (wet season)	NA		
90% Maximum pH	Ambient Stream Data (Station 5APCT001.23)		
10% Maximum pH	Ambient Stream Data (Station 5APCT001.23)		
Tier Designation	Tier Determination		
Stream Flows			
All Data	Flow Frequency Determination		
Mixing In	formation		
All Data	Mix.exe determination (30Q10) and 100% mix assumption for 0.0 MGD 1Q10 and 7Q10 flows		
Effluent II	nformation		
Mean Hardness	Default value absent of data (25 mg/L as CaCO3)		
90% Temperature (annual)	Calculated from Station 5APCT001.23 data (see Fact sheet item 16)		
90% Maximum pH	Calculated from DMR data (9.0 SU)		
10% Maximum pH	Calculated from DMR data (7.0 SU)		
Discharge flow	Design Flow (0.013 MGD)		

Data Location:

Flow Frequency Memo – Attachment A
Ambient Stream Data- see Fact sheet Item 13 and Attachment E for details
DMR data- Attachment E

mi x. txt

Mixing Zone Predictions for

Picture Lake Campground

 $\begin{array}{lll} Effl\,uent\,\,Fl\,ow\,=\,.\,013\,\,MGD\\ Stream\,\,7010\,\,\,=\,.\,0001\,\,MGD\\ Stream\,\,30010\,\,=\,0.\,01\,\,MGD\\ Stream\,\,1010\,\,\,=\,.\,0001\,\,MGD\\ Stream\,\,sl\,ope\,\,\,=\,.\,00038\,\,ft/ft\\ Stream\,\,wi\,\,dth\,\,\,=\,4\,\,ft \end{array}$

Stream width = 4 f Bottom scale = 3 Channel scale = 1

Mixing Zone Predictions @ 7Q10

Depth = .0951 ft Length = 105.26 ft Velocity = .0533 ft/sec Residence Time = .0228 days

Recommendation:

A complete $\min x$ assumption is appropriate for this situation and the entire 7Q10 may be used.

Mixing Zone Predictions @ 30Q10

Depth = .1342 ft Length = 77.98 ft Velocity = .0663 ft/sec Residence Time = .0136 days

Recommendation:

A complete $\min x$ assumption is appropriate for this situation and the entire 30Q10 may be used.

Mixing Zone Predictions @ 1010

Recommendation:

A complete $\min x$ assumption is appropriate for this situation and the entire 1Q10 may be used.

Virginia DEQ Mixing Zone Analysis Version 2.1

Note: The flow frequency analysis (Attachment A) indictaed 0.0 MGD flows for the 7Q10 and the 1Q10. Therefore, low dummy values were entered into Mix. exe to force the program to provide a mix assupmtion for the 30Q10 flow.

FRESHWATER WATER QUALITY CRITERIA / WASTELOAD ALLOCATION ANALYSIS

Facility Name: Picture Lake Campground

Permit No.: VA0070564

Receiving Stream: Picture Lake

Version: OWP Guidance Memo 00-2011 (8/24/00)

Stream Information		
Mean Hardness (as CaCO3) =	19	mg/L
90% Temperature (Annual) =	28.2	deg C
90% Temperature (Wet season) =		deg C
90% Maximum pH =	6.7	SU
10% Maximum pH =	6.1	SU
Tier Designation (1 or 2) =	1	
Public Water Supply (PWS) Y/N? =	n	
Trout Present Y/N? =	n	
Early Life Stages Present Y/N? =	у	

Stream Flows		
1Q10 (Annual) =	0	MGD
7Q10 (Annual) =	0	MGD
30Q10 (Annual) =	0.01	MGD
1Q10 (Wet season) =	0.27	MGD
30Q10 (Wet season)	0.7	MGD
30Q5 =	0.02	MGD
Harmonic Mean =		MGD

Mixing Information		
Annual - 1Q10 Mix =	100	%
- 7Q10 Mix =	100	%
- 30Q10 Mix =	100	%
Wet Season - 1Q10 Mix =		%
- 30Q10 Mix =		%

Effluent Information		
Mean Hardness (as CaCO3) =	25	mg/L
90% Temp (Annual) =	28.2	deg C
90% Temp (Wet season) =		deg C
90% Maximum pH =	9	SU
10% Maximum pH =	7	SU
Discharge Flow =	0.013	MGD

Parameter	Background		Water Qual	lity Criteria			Wasteload	Allocations		,	Antidegrada	tion Baseline		Aı	ntidegradati	on Allocations			Most Limitii	ng Allocation	s
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН
Acenapthene	5	-		na	9.9E+02			na	2.5E+03	-										na	2.5E+03
Acrolein	0			na	9.3E+00			na	2.4E+01											na	2.4E+01
Acrylonitrile ^C	0			na	2.5E+00			na	2.5E+00											na	2.5E+00
Aldrin ^C	0	3.0E+00		na	5.0E-04	3.0E+00		na	5.0E-04									3.0E+00		na	5.0E-04
Ammonia-N (mg/l) (Yearly)	0	4.005.00	0.005.00			4.005.00	4.005.00											4.005.00	4.005.00		
Ammonia-N (mg/l)	0	1.32E+00	2.39E+00	na		1.32E+00	4.23E+00	na										1.32E+00	4.23E+00	na	-
(High Flow)	0	1.32E+00	4.86E-01	na		1.32E+00	4.86E-01	na										1.32E+00	4.86E-01	na	
Anthracene	0			na	4.0E+04			na	1.0E+05											na	1.0E+05
Antimony	0			na	6.4E+02			na	1.6E+03											na	1.6E+03
Arsenic	0	3.4E+02	1.5E+02	na		3.4E+02	1.5E+02	na										3.4E+02	1.5E+02	na	
Barium	0			na				na												na	
Benzene ^C	0			na	5.1E+02			na	5.1E+02											na	5.1E+02
Benzidine ^C	0			na	2.0E-03			na	2.0E-03											na	2.0E-03
Benzo (a) anthracene ^C	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
Benzo (b) fluoranthene ^C	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
Benzo (k) fluoranthene ^C	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
Benzo (a) pyrene ^C	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
Bis2-Chloroethyl Ether C	0			na	5.3E+00			na	5.3E+00											na	5.3E+00
Bis2-Chloroisopropyl Ether	0			na	6.5E+04			na	1.7E+05											na	1.7E+05
Bis 2-Ethylhexyl Phthalate ^C	0			na	2.2E+01			na	2.2E+01											na	2.2E+01
Bromoform ^C	0			na	1.4E+03			na	1.4E+03											na	1.4E+03
Butylbenzylphthalate	0			na	1.9E+03			na	4.8E+03											na	4.8E+03
Cadmium	0	8.2E-01	3.8E-01	na		8.2E-01	3.8E-01	na										8.2E-01	3.8E-01	na	
Carbon Tetrachloride C	0			na	1.6E+01			na	1.6E+01											na	1.6E+01
Chlordane ^C	0	2.4E+00	4.3E-03	na	8.1E-03	2.4E+00	4.3E-03	na	8.1E-03									2.4E+00	4.3E-03	na	8.1E-03
Chloride	0	8.6E+05	2.3E+05	na		8.6E+05	2.3E+05	na										8.6E+05	2.3E+05	na	
TRC	0	1.9E+01	1.1E+01	na		1.9E+01	1.1E+01	na										1.9E+01	1.1E+01	na	
Chlorobenzene	0			na	1.6E+03			na	4.1E+03											na	4.1E+03

Parameter	Background		Water Qua	lity Criteria			Wasteload	Allocations		,	Antidegrada	tion Baseline		Ar	ntidegradation	on Allocations			Most Limitir	ng Allocations	s
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН
Chlorodibromomethane ^C	0			na	1.3E+02			na	1.3E+02	-										na	1.3E+02
Chloroform	0			na	1.1E+04			na	2.8E+04											na	2.8E+04
2-Chloronaphthalene	0			na	1.6E+03			na	4.1E+03											na	4.1E+03
2-Chlorophenol	0			na	1.5E+02			na	3.8E+02											na	3.8E+02
Chlorpyrifos	0	8.3E-02	4.1E-02	na		8.3E-02	4.1E-02	na										8.3E-02	4.1E-02	na	-
Chromium III	0	1.8E+02	2.4E+01	na		1.8E+02	2.4E+01	na										1.8E+02	2.4E+01	na	
Chromium VI	0	1.6E+01	1.1E+01	na		1.6E+01	1.1E+01	na										1.6E+01	1.1E+01	na	
Chromium, Total	0			1.0E+02				na												na	
Chrysene ^C	0			na	1.8E-02			na	1.8E-02											na	1.8E-02
Copper	0	3.6E+00	2.7E+00	na		3.6E+00	2.7E+00	na										3.6E+00	2.7E+00	na	
Cyanide, Free	0	2.2E+01	5.2E+00	na	1.6E+04	2.2E+01	5.2E+00	na	4.1E+04									2.2E+01	5.2E+00	na	4.1E+04
DDD ^C	0	2.22.01		na	3.1E-03	2.22.01		na	3.1E-03											na	3.1E-03
DDE c	0			na	2.2E-03			na	2.2E-03											na	2.2E-03
DDT ^c	0	1 15±00	1.0E-03		2.2E-03	1.1E+00	1.0E-03		2.2E-03					-				1.1E+00	1.0E-03		2.2E-03 2.2E-03
		1.1E+00		na				na												na	
Demeton	0	 4.7E.04	1.0E-01	na		4.75.04	1.0E-01	na										4.75.04	1.0E-01	na	
Diazinon Dibenz(a,h)anthracene ^C	0	1.7E-01	1.7E-01	na		1.7E-01	1.7E-01	na										1.7E-01	1.7E-01	na	
	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
1,2-Dichlorobenzene	0			na	1.3E+03			na	3.3E+03									-		na	3.3E+03
1,3-Dichlorobenzene	0			na	9.6E+02			na	2.4E+03											na	2.4E+03
1,4-Dichlorobenzene	0			na	1.9E+02			na	4.8E+02											na	4.8E+02
3,3-Dichlorobenzidine ^C	0			na	2.8E-01			na	2.8E-01											na	2.8E-01
Dichlorobromomethane ^C	0			na	1.7E+02			na	1.7E+02									-		na	1.7E+02
1,2-Dichloroethane ^C	0			na	3.7E+02			na	3.7E+02											na	3.7E+02
1,1-Dichloroethylene	0			na	7.1E+03			na	1.8E+04											na	1.8E+04
1,2-trans-dichloroethylene	0			na	1.0E+04			na	2.5E+04											na	2.5E+04
2,4-Dichlorophenol	0			na	2.9E+02			na	7.4E+02											na	7.4E+02
2,4-Dichlorophenoxy acetic acid (2,4-D)	0			na				na												na	
1,2-Dichloropropane ^C	0			na	1.5E+02			na	1.5E+02											na	1.5E+02
1,3-Dichloropropene ^C	0			na	2.1E+02			na	2.1E+02											na	2.1E+02
Dieldrin ^C	0	2.4E-01	5.6E-02	na	5.4E-04	2.4E-01	5.6E-02	na	5.4E-04									2.4E-01	5.6E-02	na	5.4E-04
Diethyl Phthalate	0			na	4.4E+04			na	1.1E+05											na	1.1E+05
2,4-Dimethylphenol	0			na	8.5E+02			na	2.2E+03											na	2.2E+03
Dimethyl Phthalate	0			na	1.1E+06			na	2.8E+06											na	2.8E+06
Di-n-Butyl Phthalate	0			na	4.5E+03			na	1.1E+04										-	na	1.1E+04
2,4 Dinitrophenol	0			na	5.3E+03			na	1.3E+04										-	na	1.3E+04
2-Methyl-4,6-Dinitrophenol	0			na	2.8E+02			na	7.1E+02					-						na	7.1E+02
2,4-Dinitrotoluene ^C	0	-		na	3.4E+01			na	3.4E+01						-					na	3.4E+01
Dioxin 2,3,7,8-	U			па	3.4⊑+01			IId	3.4⊑+01											IIđ	3.4⊑*01
tetrachlorodibenzo-p-dioxin	0			na	5.1E-08			na	1.3E-07											na	1.3E-07
1,2-Diphenylhydrazine ^C	0			na	2.0E+00			na	2.0E+00											na	2.0E+00
Alpha-Endosulfan	0	2.2E-01	5.6E-02	na	8.9E+01	2.2E-01	5.6E-02	na	2.3E+02									2.2E-01	5.6E-02	na	2.3E+02
Beta-Endosulfan	0	2.2E-01	5.6E-02	na	8.9E+01	2.2E-01	5.6E-02	na	2.3E+02									2.2E-01	5.6E-02	na	2.3E+02
Alpha + Beta Endosulfan	0	2.2E-01	5.6E-02			2.2E-01	5.6E-02											2.2E-01	5.6E-02		
Endosulfan Sulfate	0			na	8.9E+01			na	2.3E+02											na	2.3E+02
Endrin	0	8.6E-02	3.6E-02	na	6.0E-02	8.6E-02	3.6E-02	na	1.5E-01									8.6E-02	3.6E-02	na	1.5E-01
Endrin Aldehyde	0			na	3.0E-01			na	7.6E-01											na	7.6E-01

Parameter	Background		Water Qual	lity Criteria			Wasteload	Allocations		,	Antidegrada	ation Baseline		A	ntidegradation	Allocations			Most Limitin	g Allocations	<u> </u>
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic I	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН
Ethylbenzene	0			na	2.1E+03			na	5.3E+03											na	5.3E+03
Fluoranthene	0			na	1.4E+02			na	3.6E+02											na	3.6E+02
Fluorene	0			na	5.3E+03			na	1.3E+04											na	1.3E+04
Foaming Agents	0			na				na												na	
Guthion	0		1.0E-02	na			1.0E-02	na											1.0E-02	na	
Heptachlor ^C	0	5.2E-01	3.8E-03	na	7.9E-04	5.2E-01	3.8E-03	na	7.9E-04									5.2E-01	3.8E-03	na	7.9E-04
Heptachlor Epoxide ^C	0	5.2E-01	3.8E-03	na	3.9E-04	5.2E-01	3.8E-03	na	3.9E-04							_		5.2E-01	3.8E-03	na	3.9E-04
Hexachlorobenzene ^C	0	3.2L-01	3.0L-03	na	2.9E-03	J.ZL-01	3.0L-03	na	2.9E-03		_					_		3.2L-01	3.0L-03	na	2.9E-03
Hexachlorobutadiene ^C	0				1.8E+02				1.8E+02									-			1.8E+02
Hexachlorocyclohexane	U			na	1.00702			na	1.00+02									-		na	1.02702
Alpha-BHC ^C	0			na	4.9E-02			na	4.9E-02											na	4.9E-02
Hexachlorocyclohexane																					
Beta-BHC ^C	0			na	1.7E-01			na	1.7E-01											na	1.7E-01
Hexachlorocyclohexane																					
Gamma-BHC ^C (Lindane)	0	9.5E-01	na	na	1.8E+00	9.5E-01		na	1.8E+00									9.5E-01		na	1.8E+00
Hexachlorocyclopentadiene	0			na	1.1E+03			na	2.8E+03									-		na	2.8E+03
Hexachloroethane ^C	0			na	3.3E+01			na	3.3E+01											na	3.3E+01
Hydrogen Sulfide	0		2.0E+00	na			2.0E+00	na											2.0E+00	na	-
Indeno (1,2,3-cd) pyrene ^C	0			na	1.8E-01			na	1.8E-01											na	1.8E-01
Iron	0			na				na												na	
Isophorone ^C	0			na	9.6E+03			na	9.6E+03											na	9.6E+03
Kepone	0		0.0E+00	na			0.0E+00	na											0.0E+00	na	
Lead	0	2.0E+01	2.3E+00	na		2.0E+01	2.3E+00	na										2.0E+01	2.3E+00	na	
Malathion	0		1.0E-01	na			1.0E-01	na											1.0E-01	na	
Manganese	0			na				na												na	
Mercury	0	1.4E+00	7.7E-01			1.4E+00	7.7E-01									_		1.4E+00	7.7E-01		
•	0	1.42.00	7.72-01	na	1.5E+03	1.42.00	7.7L-01		3.8E+03									1.42.00	7.7 L-0 1	na	3.8E+03
Methyl Bromide Methylene Chloride ^C	0			na	5.9E+03			na na	5.9E+03											na	5.9E+03
	0																				
Methoxychlor		-	3.0E-02	na			3.0E-02	na			-								3.0E-02	na	-
Mirex	0		0.0E+00	na			0.0E+00	na											0.0E+00	na	
Nickel	0	5.6E+01	6.3E+00	na	4.6E+03	5.6E+01	6.3E+00	na	1.2E+04		-							5.6E+01	6.3E+00	na	1.2E+04
Nitrate (as N)	0			na				na												na	-
Nitrobenzene	0			na	6.9E+02			na	1.8E+03											na	1.8E+03
N-Nitrosodimethylamine ^C	0			na	3.0E+01			na	3.0E+01									-		na	3.0E+01
N-Nitrosodiphenylamine ^C	0			na	6.0E+01			na	6.0E+01											na	6.0E+01
N-Nitrosodi-n-propylamine ^C	0			na	5.1E+00			na	5.1E+00											na	5.1E+00
Nonylphenol	0	2.8E+01	6.6E+00			2.8E+01	6.6E+00	na										2.8E+01	6.6E+00	na	
Parathion	0	6.5E-02	1.3E-02	na		6.5E-02	1.3E-02	na										6.5E-02	1.3E-02	na	
PCB Total ^C	0		1.4E-02	na	6.4E-04		1.4E-02	na	6.4E-04										1.4E-02	na	6.4E-04
Pentachlorophenol ^C	0	8.7E+00	6.7E+00	na	3.0E+01	8.7E+00	6.7E+00	na	3.0E+01									8.7E+00	6.7E+00	na	3.0E+01
Phenol	0			na	8.6E+05			na	2.2E+06											na	2.2E+06
Pyrene	0			na	4.0E+03			na	1.0E+04											na	1.0E+04
Radionuclides	0			na				na												na	-
Gross Alpha Activity	_																				
(pCi/L)	0			na				na												na	
Beta and Photon Activity (mrem/yr)	0			na	4.0E+00			na	1.0E+01											na	1.0E+01
Radium 226 + 228 (pCi/L)	0			na				na												na	
Uranium (ug/l)	0										-		-							na	
Gramani (ag/i)	U	-		na				na												IId	

Parameter	Background		Water Qua	lity Criteria			Wasteload	Allocations			Antidegrada	tion Baseline		Aı	ntidegradati	on Allocations			Most Limiti	ng Allocation	s
(ug/l unless noted)	Conc.	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	НН	Acute	Chronic	HH (PWS)	нн
Selenium, Total Recoverable	0	2.0E+01	5.0E+00	na	4.2E+03	2.0E+01	5.0E+00	na	1.1E+04									2.0E+01	5.0E+00	na	1.1E+04
Silver	0	3.2E-01		na		3.2E-01		na										3.2E-01		na	
Sulfate	0			na				na												na	
1,1,2,2-Tetrachloroethane ^C	0			na	4.0E+01			na	4.0E+01											na	4.0E+01
Tetrachloroethylene ^C	0			na	3.3E+01			na	3.3E+01											na	3.3E+01
Thallium	0			na	4.7E-01			na	1.2E+00											na	1.2E+00
Toluene	0			na	6.0E+03			na	1.5E+04											na	1.5E+04
Total dissolved solids	0			na				na												na	
Toxaphene ^C	0	7.3E-01	2.0E-04	na	2.8E-03	7.3E-01	2.0E-04	na	2.8E-03									7.3E-01	2.0E-04	na	2.8E-03
Tributyltin	0	4.6E-01	7.2E-02	na		4.6E-01	7.2E-02	na										4.6E-01	7.2E-02	na	
1,2,4-Trichlorobenzene	0			na	7.0E+01			na	1.8E+02											na	1.8E+02
1,1,2-Trichloroethane ^C	0			na	1.6E+02			na	1.6E+02											na	1.6E+02
Trichloroethylene ^C	0			na	3.0E+02			na	3.0E+02											na	3.0E+02
2,4,6-Trichlorophenol ^C	0			na	2.4E+01			na	2.4E+01											na	2.4E+01
2-(2,4,5-Trichlorophenoxy) propionic acid (Silvex)	0	-		na				na												na	-
Vinyl Chloride ^C	0			na	2.4E+01			na	2.4E+01											na	2.4E+01
Zinc	0	3.6E+01	3.6E+01	na	2.6E+04	3.6E+01	3.6E+01	na	6.6E+04									3.6E+01	3.6E+01	na	6.6E+04

Notes:

- 1. All concentrations expressed as micrograms/liter (ug/l), unless noted otherwise
- 2. Discharge flow is highest monthly average or Form 2C maximum for Industries and design flow for Municipals
- 3. Metals measured as Dissolved, unless specified otherwise
- 4. "C" indicates a carcinogenic parameter
- Regular WLAs are mass balances (minus background concentration) using the % of stream flow entered above under Mixing Information. Antidegradation WLAs are based upon a complete mix.
- 6. Antideg. Baseline = (0.25(WQC background conc.) + background conc.) for acute and chronic
 - = (0.1(WQC background conc.) + background conc.) for human health
- 7. WLAs established at the following stream flows: 1Q10 for Acute, 30Q10 for Chronic Ammonia, 7Q10 for Other Chronic, 30Q5 for Non-carcinogens and Harmonic Mean for Carcinogens. To apply mixing ratios from a model set the stream flow equal to (mixing ratio 1), effluent flow equal to 1 and 100% mix.

		_
Metal	Target Value (SSTV)	Ν
Antimony	1.6E+03	n
Arsenic	9.0E+01	g
Barium	na	
Cadmium	2.3E-01	
Chromium III	1.4E+01	
Chromium VI	6.4E+00	
Copper	1.5E+00	
Iron	na	
Lead	1.4E+00	
Manganese	na	
Mercury	4.6E-01	
Nickel	3.8E+00	
Selenium	3.0E+00	
Silver	1.3E-01	
Zinc	1.4E+01	

Note: do not use QL's lower than the minimum QL's provided in agency quidance

Stats.exe Results

Facility = Picture Lake Campground

Chemical = Ammonia

Chronic averaging period = 30

WLAa = 1.32 WLAc = 4.23 Q.L. = 0.2 # samples/mo. = 1 # samples/wk. = 1

Summary of Statistics:

observations = 1
Expected Value = 9
Variance = 29.16
C.V. = 0.6

97th percentile daily values = 21.9007 97th percentile 4 day average = 14.9741 97th percentile 30 day average = 10.8544

< Q.L. = 0

Model used = BPJ Assumptions, type 2 data

A limit is needed based on Acute Toxicity

Maximum Daily Limit = 1.32 Average Weekly limit = 1.32 Average Monthly Limit = 1.32

The data are:

9.00 mg/L

Per GM 00-2011 a datum of 9.00 mg/L is used to force an ammonia limit. This limitation is more stringent than the 2006 permit limitation.

Facility = Picture Lake Campground

Chemical = TRC

Chronic averaging period = 4

WLAa = 19 WLAc = 11 Q.L. = 100 # samples/mo. = 30 # samples/wk. = 7

Summary of Statistics:

observations = 1 Expected Value = 20000 Variance = 1440000 C.V. = 0.6

97th percentile daily values = 48668.3 97th percentile 4 day average = 33275.8 97th percentile 30 day average = 24121.0

< Q.L. = 0

Model used = BPJ Assumptions, type 2 data

A limit is needed based on Chronic Toxicity
Maximum Daily Limit = 16.0883226245855
Average Weekly limit = 9.8252545713861
Average Monthly LImit = 7.9737131838758

The data are:

20000 μg/L

Per GM 00-2011 a datum of 20,000 μ g/L is used to force a TRC limit. The resulting limit is the same as the 2006 permit.

Attachment G: S	Stream Sanitati	on Memorar	ndum (4/12/1	991)
Attachment G.	Stream Garitati	on wemora	iddiii (4 /12/1	551)

MEMORANDUM

SUBJECT:

Effluent Limits for Picture Lake Campground & Green Acre

Mobile Home Park, Discharge to Picture Run then to Hatcher

Run, Dinwiddie County, James River Basin

TO:

[Chowan] Doz Aurt Linderman via Golam Mustafa Golam Mustafer

FROM:

D. X. Ren

DATE:

April 12, 1991

COPIES:

Diane Osborne, Jody Bryan, File

Purpose of Study:

The modeling efforts were caused by an inconsistency regarding DO limits in the existing modeling files of these above two subject facilities. This memo is to verify and determine appropriate effluent limits for the subject discharges.

Site Inspection:

A site inspection was conducted by me on March 28, 1991. Picture Lake Campground is currently owned by H & B, Inc., and is located downstream of a dam. The Green Acre MHP discharge is located 0.3 mile downstream of Picture Lake Campground STP. Picture Run runs 0.93 mile from Green Acre MHP and joins with Hatcher Run. Hatcher Run comes from Jordan Lake and ends at Steers Millpond. The two subject discharges are eventually contained in Steers Millpond. Site inspection indicated that Picture Run currently maintains a good or fair water quality (see Attachment-A).

7010 Flow Estimates:

According to the information in the existing modeling files, the critical flow used in previous modeling was 0.0337 cfs or 0.0218 MGD ac the discharge point of Picture Lake Campground. In 1991, OWRP utilized a partial streamflow recording station on Whipponock Creek at Route 627 near Church Road (02041400) to synthesize critical flow for these discharges. This station was chosen on the basis of proximity, and, similarity in watershed size and topography (see Attachment-B).

Page 2 Picture Lake Campground and Green Acre MHP

The characteristics for the Whipponock station are:

Drainage area = 3.27 square miles

7Q10 flow = 0.01 cfs

7Q10 runoff = 0.0031 cfs/m^2

For the above two discharge points:

H & B of Virginia: Drainage area = 3.5 square miles

7Q10 flow = 0.01 cfs or 0.007 MGD

Green Area MHP: Drainage area = 3.73 square miles

7Q10 flow = 0.011 cfs or 0.007 MGD

My site inspection indicated that Picture Lake Campground STP discharges to Picture Run just 100 feet downstream of the dam. releases water via a spray nozzle. According to the operator, during the summer season, the dam reduces water flow. OWRP's flow analysis assumed outflow from the impoundment equalled inflow to the Lake. It is possible that actual low flow for this stream could be different from OWRP's calculated 7Q10 flow due to the effect on flows of the Investigation of the use of the Deep Creek (02041000) and impoundment. Stony Creek (02046000) continuous recording gaging stations as reference gages would result in a larger 7010 flow range than the partial record station. In the absence of low flow data past the impoundment, it was decided to keep consistency with the previous efforts and use a 7010 value of 0.0337 cfs or 0.0218 MGD to rerun the model. This decision was made with consultation with OWRP. value was previously used for simulating Picture Run.

Antidegradation Policy:

The modeling records made in 1977 indicated that antidegradation policy was not applied in both subject files.

Modeling Approach:

According to PRO modeling files, the latest modeling effort was made in March 1977. In 1986, Paul Herman applied the same limits except facility design flow to process a permit planning statement. No model was run at that time. The Streeter-Phelps Model of Monroe version was rerun to verify the effluent limits for the two discharges. Also the Steady State Model (version 5.0, 1990) was generated based on all previous assumptions for comparison.

Page 3 Picture Lake Campground and Green Acre MHP

Modeling Results:

The following effluent limits are acceptable:

Picture Lake Campground

$$Q = 0.013 \text{ MGD}$$
 $BOD_{5} = 30.0 \text{ mg/l}$
 $DO = 6.0 \text{ mg/l}$
 $BOD_{4}/BOD_{5} = 1.58$

Green Acre Mobile Home Park

The computer printout, copy of topographic map, and schematic showing the discharge points are attached for your reference.

If you have any questions, please let me know.

Attachments

Attachment	H: Operator	Training and	Assistance	Program



Operator Training and Assistance Report Picture Lake Campground VPDES Permit #VA0070564

Project Overview:

During the period from August 2009 through February 2010, the Office of Water Permits and Compliance Assistance, Operator Training program staff conducted an on-site training and assistance program at the Picture Lake Campground (PLC) wastewater treatment plant (WWTP). The program was a result of a recommendation by Piedmont Regional Office (PRO) compliance inspector Michael Dare and a request from PLC owner/operator, Ryan Porter. The activities of the Operator Training program are documented in this Training and Assistance Report (TAR).

Comprehensive Performance Evaluation:

On August 18, 2009, Jason Spicer, DEQ-Operator Training Program performed a comprehensive performance evaluation (CPE) of the PLC WWTP to assess treatment plant performance and evaluate the facility for inclusion in DEQ's operator training and assistance program. A copy of the full evaluation report is available on the enterprise content management system (ECM).

The evaluation identified the following performance limiting factors (PLF's) with process operations at the facility:

- ➤ The facility had been out of compliance with its VPDES permit for several months.
- ➤ It appeared the facility was not achieving nitrification resulting in Ammonia-N levels in excess of VPDES permit limitation.
- Process control sampling and testing was not being performed at the facility.
- ➤ The plant lacked a clearly defined Standard Operating Procedure (SOP) for the operation and maintenance of the treatment facility.

The best mechanism for addressing the performance limiting factors was determined to be an on-site training and assistance program.

Training and Assistance Activities:

A training and assistance plan was developed for the facility. A copy of the complete training plan is available on the ECM. The specific objectives of the training and assistance plan were to:

- ➤ Develop and implement standard operating procedures (SOPs) for process control of the activated sludge system to ensure compliance with applicable federal and state regulations.
- ➤ Develop and implement VPDES reporting procedures that meet all applicable permit requirements.

Training and assistance visits were made to the plant on September 29, 2009 and December 10, 2009. In addition, program staff provided assistance through phone, email and other electronic means (i.e., text). The PLC WWTP personnel had successfully completed the activities specified in the training and assistance plan and the project was completed on March 1, 2010.

After the project was completed, campground staff continued to request assistance regularly, with operations, as changes in the plant occurred. Since the operator training program staff do not act as the operator in responsible charge, a recommendation was made to campground management that they consider consulting a licensed contract operator to assist them with making daily operational adjustments to the process.

Accomplishments:

The following accomplishments are direct or indirect results of training and assistance received during the project:

- ➤ The facility was in compliance with its permit limit for Ammonia, and all other permit requirements, during the project activity months of August and October 2009 and from December 2009 March 2010 consecutively. Sampling and testing data is presented as Attachment 1.
- ➤ The campground staff recognizes the importance of properly operating and maintaining the treatment system.
- The campground staff has initiated a SOP for all plant activities and is performing and documenting process control tests on a regular basis.
- ➤ The campground owner/operator has hired a licensed operator/consultant to assist him with the day to day plant operations.

Project Status:

- ➤ The campground owner has hired a contract operator.
- ➤ The Operator Training and Assistance program staff has no plans to provide onsite assistance to the campground at this time.

Attachment 1 : Picture Lake Campground DMR Data 2009 - 2010

	2009			2010	
Month	Ammonia, mg/L	Ammonia, mg/L	Month	Ammonia, mg/L	Ammonia, mg/L
	Average	Max		Average	Max
January	In April 2009, the	facility ammonia	January	0.23	0.23
February	limit went from	an interim limit	February	0.14	0.14
March	(4.0 mg/L) to th mg.		March	0.46	0.46
April			April	2.5	<mark>2.7</mark>
May	<mark>9.5</mark>	<mark>18.8</mark>	May	<mark>7.96</mark>	<mark>7.96</mark>
June	<mark>3.1</mark>	<mark>3.1</mark>	June	<mark>40.6</mark>	<mark>40.6</mark>
July	<mark>15.6</mark>	<mark>16.9</mark>	July	0.40	0.40
August	0.10	0.10	August	0.16	0.16
September	<mark>3.55</mark>	<mark>3.55</mark>	September	0.37	0.37
October	1.06	1.06	October	0.57	0.57
November	<mark>26.5</mark>	<mark>51.5</mark>	November	<mark>2.86</mark>	<mark>2.86</mark>
December	1.78 1.78		December	>0.1	>0.1

- > Areas with no shading (White) represent campground operations prior to and after DEQ training program guidance
- > The Light Gray shaded areas represent campground operations with DEQ training program guidance
- > The Dark Gray shaded areas represent campground operations with contractor assistance
- > The Yellow shaded numbers represent a permit exceedance

Attachment I: Threatened and Endangered Species Coord	dination



COMMONWEALTH of VIRGINIA

DEPARTMENT OF CONSERVATION AND RECREATION

Division of Natural Heritage 217 Governor Street Richmond, Virginia 23219-2010 (804) 786-7951 MEMORANDUM

DATE: March 14, 2011

TO: Janine Howard, DEQ-PRO

FROM: Rene' Hypes, DCR-DNH

SUBJECT: VA0070564, Picture Lake Campground WWTP

The Department of Conservation and Recreation's Division of Natural Heritage (DCR) has searched its Biotics Data System for occurrences of natural heritage resources from the area outlined on the submitted map. Natural heritage resources are defined as the habitat of rare, threatened, or endangered plant and animal species, unique or exemplary natural communities, and significant geologic formations.

Biotics historically documents the presence of natural heritage resources in the project area. However, due to the scope of the activity and the distance to the resources, we do not anticipate that this project will adversely impact these natural heritage resources.

Under a Memorandum of Agreement established between the Virginia Department of Agriculture and Consumer Services (VDACS) and the Virginia Department of Conservation and Recreation (DCR), DCR represents VDACS in comments regarding potential impacts on state-listed threatened and endangered plant and insect species. The current activity will not affect any documented state-listed plants or insects.

In addition, our files do not indicate the presence of any State Natural Area Preserves under DCR's jurisdiction in the project vicinity.

New and updated information is continually added to Biotics. Please contact DCR for an update on this natural heritage information if a significant amount of time passes before it is utilized.

The Virginia Department of Game and Inland Fisheries maintains a database of wildlife locations, including threatened and endangered species, trout streams, and anadromous fish waters that may contain information not documented in this letter. Their database may be accessed from http://vafwis.org/fwis/ or contact Shirl Dressler at (804) 367-6913.

Thank you for the opportunity to comment on this project.





Virginia Department of Game and Inland Fisheries

3/22/2011 10:32:06 AM

Fish and Wildlife Information Service

VaFWIS Search Report Compiled on 3/22/2011, 10:32:06 AM 330431.0

Help

Known or likely to occur within a 2 mile radius of null (at 37,09,41.8 -77,30,59.8) in 053 Dinwiddie County, VA

115 Known or Likely Species ordered by Status Concern for Conservation (displaying first 20) (5 species with Status* or Tier I**)

BOVA Code	Status*	<u>Tier**</u>	<u>Common</u> <u>Name</u>	Scientific Name	Confirmed	Database(s)
010214	FESE	I	Logperch, Roanoke	Percina rex	Potential	Habitat,BOVA,HU6
010347	SE	I	Sunfish, blackbanded	Enneacanthus chaetodon	Potential	Habitat,HU6
060081	ST	II	Floater, green	Lasmigona subviridis		HU6
070105	FS	III	Crayfish, Chowanoke	Orconectes virginiensis		BOVA,HU6
010077		I	Shiner, bridle	Notropis bifrenatus		BOVA
010174		II	Bass, Roanoke	Ambloplites cavifrons	<u>Potential</u>	Habitat,BOVA,HU6
010032		II	Sturgeon, Atlantic	Acipenser oxyrinchus		BOVA
020082		III	Siren, eastern lesser	Siren intermedia intermedia		HU6
020022	A Commence of the Commence of	III	Waterdog, dwarf	Necturus punctatus	A The state of the	BOVA,HU6
060145		III	Rainbow, notched	Villosa constricta	2 d	BOVA
010038	A A A A A A A A A A A A A A A A A A A	IV	Alewife	Alosa pseudoharengus	**************************************	BOVA,HU6
010131		IV	Eel, American	Anguilla rostrata	Yes	Collections,BOVA,HU6
010359		IV	Lamprey, American brook	Lampetra appendix		HU6
010040	VIVINGENIES CONTRACTOR OF THE PROPERTY OF THE	IV	Shad, American	Alosa sapidissima		BOVA,HU6
010375		IV	Shiner, ironcolor	Notropis chalybaeus	ediziono diazamonistra	BOVA

010179	IV	Sunfish, banded	Enneacanthus obesus	BOVA,HU6
010173	IV	Sunfish, mud	Acantharchus pomotis	BOVA,HU6
010149	IV	Swampfish	Chologaster cornuta	HU6
020069	IV	Salamander, eastern mud	Pseudotriton montanus montanus	BOVA,HU6
020034	IV	Salamander, many-lined	Stereochilus marginatus	HU6

To view All 115 species View 115

audit no. 330431 3/22/2011 10:32:06 AM Virginia Fish and Wildlife Information Service © 1998-2011 Commonwealth of Virginia Department of Game and Inland Fisheries

^{*} FE=Federal Endangered; FT=Federal Threatened; SE=State Endangered; ST=State Threatened; FP=Federal Proposed; FC=Federal Candidate; FS=Federal Species of Concern; SC=State Candidate; CC=Collection Concern; SS=State Special Concern (obsolete January 1, 2011)

^{**} I=VA Wildlife Action Plan - Tier I - Critical Conservation Need; II=VA Wildlife Action Plan - Tier II - Very High Conservation Need; III=VA Wildlife Action Plan - Tier III - High Conservation Need; IV=VA Wildlife Action Plan - Tier IV - Moderate Conservation Need